



# LITOSTRIP

## CLEANING GEL TO REMOVE EPOXY MORTAR RESIDUES

### DESCRIPTION

LITOSTRIP is a clear gel consisting of a mix of solvents easily applied with a squeegee or a brush on horizontal and vertical surfaces

### FIELDS OF APPLICATION

LITOSTRIP is a product designed to completely remove hardened STARLIKE® or EPOXYSTUK X90 based epoxy grouting residues within gaps, or stains that are present on the ceramic surface due to incorrect or incomplete cleaning.

### APPLICATION

The product is ready to use and does not need to be diluted. Apply a thin layer evenly on the affected area using a brush or steel trowel. Leave to work until the residues become soft and ready to be easily removed. Usually, 10-20 minutes are enough; in case of tough marks and grout residues leave for 1-8 hours.

Afterwards, remove the epoxy mortar residues using the steel trowel. Use a clean dry cloth to remove the gel and rinse with

plenty of clean water. If necessary, repeat the cleaning process twice.

### WARNINGS

- Do not dilute the product with water or solvents
- Do not use if the surface to be treated is not resistant to solvents, for example: plastic materials, PVC, linoleum, enamel, etc.
- When applied to polished tiles and polished natural stone, test the product on a small area first to check that it doesn't damage the finish
- Handle the product with care as it is extremely flammable
- Do not smoke during use
- Read the Safety Card before use
- In case of spillage, isolate the area and try to pick up as much of the product as possible and reuse it. Rinse the area with water

### PACKAGING

0.75 litre metal containers

### IDENTIFICATION DATA

Appearance	Gel
Colour	Clear
Odour	Unique to product
Custom code	3814 00 90
Flammability	Yes
Shelf life	24 months in original packaging in a cool dry place

### APPLICATION DATA

Waiting time to remove marks	Marks: 10-20 minutes Hardened grouting: 1-8 hours
Application temperature	From +5°C to +35°C
Consumption	Variable, depending on use. On average approx ca 0.1-0.3 l/m <sup>2</sup>

### SAFETY INFORMATION

Consult the Material Safety Data Sheet, available on request.

PRODUCT FOR PROFESSIONAL USE.

Although the information provided on this technical sheet represents the best of our knowledge and experience, it is intended purely as a guideline.  
The user must carry out preliminary practical tests for each specific job and is solely responsible for the final result.

Sheet n. 313

Revision n. 2

Date: March 2012

### LITOKOL S.p.A.

Via G. Falcone, 13/1 42048 Rubiera (RE) Italy  
Tel. +39 0522 622811 Fax +39 0522 620150  
www.litokol.it email: info@litokol.it